

AL1R SPECIFICATIONS	
Description	
	Full Range
	Powered
	2-way 10"
Mixer Inputs	nom. input level
Mic 1 (XLR)	-40 dBm
Mic 2 (XLR)	-40 dBm
Line (1/4")	-20 dBm
CD/Tape (2xRCA)	-20 dBV
Power Amplifier	
Power @ 8 Ohms	65 W FTC
Power @ 4 Ohms	100, 400, 1k, 3k, 6k, Hz
Distortion	<0.05%
Signal-to-Noise Ratio	>90 dB
Frequency Response	65-20k Hz
Speaker Impedance	8 Ohms
Sensitivity (1W/1m)	97 dB
Dimensions "(mm)	
Height (less handle)	21.0(533)
Width	13.0(330)
Depth	12.87(327)
Net Weight lbs. (kg)	35.4(19.3)
Components	
Woofers	STS110.8HP
Tweeter	TLX-1
Crossover	CXX12
Mixer Module	1520 5001
Amp/EQ Module	MC100
Pole Mount	SMB36



AL1R's PivotMix panel lets you attach and control professional or semi-pro microphones, CD, cassette, or DAT players, electro-acoustic guitars, keyboards...virtually any performance device. Factory-mounted in knobs-up orientation, it is easily switched to knobs-on-back orientation for easy reach when stand mounted



It's Simple, We Sound Better!

*All prices and specifications are subject to change without prior notification.