

TIME LAPSE VCR's

Whatever your application, you will find the ideal recorder in the Lorex line of Professional Time Lapse VCR's. All Lorex Time Lapse VCR's include a ball bearing capstan motor, which provides the LONGEST MOTOR LIFE - 250% - 800% longer life compared to Time Lapse VCR's units with standard motors.

Other standard features included with Lorex Time Lapse VCR's include: Digital shuttle with 6 selectable modes, 40 hour real time recording, selectable time recording options, power loss memory, on screen programming, built in rechargeable battery, reverse play option, selectable audio recording modes, quick start recording and multi-voltage capability.

Select from a 40 hour real time, 960 hour / 40 hour real time or a 960 hour / 40 hour real time with computer control time lapse VCR.

RS232C Interface allows
for Computer Control



SG7970 - 960 Hour Time Lapse VCR with Digital Shuttle and Computer Control

- 960 hour time lapse VCR - 40 hour real time / 1280 hour recording
- Built-in RS232C jack allows for computer interface
- Digital shuttle with 6 selectable settings
- 14 selectable recording options
- Reverse play option
- Built-in rechargeable back up battery (up to 1 month)
- Record lock prevents unauthorized operation
- Easy to use on screen programming
- Power loss memory (most recent 35 events)
- Warning buzzer alarm signal and end of tape
- Four selectable audio recording settings
- Four selectable recording modes; alarm, panic, repeat and timer
- Instant record check
- Multi-voltage (100 - 240 volts)
- Compatible with most Multiplexer units
- Quick start recording
- Alarm recording mode (most recent 35 events)
- UPC Code 7 78597 07970 8



SG7964 - 960 Hour Time Lapse VCR with Digital Shuttle

- 960 hour time lapse VCR - 40 hour real time / 1280 hour recording
- Digital shuttle with 6 selectable recording settings
- 14 selectable recording options
- Reverse play option
- Built-in rechargeable back up battery (up to 1 month)
- Record lock prevents unauthorized operation
- Easy to use on screen programming
- Power loss memory (most recent 35 events)
- Warning buzzer alarm signal and end of tape
- Four selectable audio recording settings
- Four selectable recording modes; alarm, panic, repeat and timer
- Instant record check
- Multi-voltage (100 - 240 volts)
- Compatible with most Multiplexer units
- Quick start recording
- Alarm recording mode (most recent 35 events)
- UPC Code 7 78597 07964 7

www.strategicvista.com

SEE WHAT YOU'VE BEEN MISSING



TIME LAPSE VCR's



SG7940 - Time Lapse VCR - 40 Hour Real Time

- 40 hour real time / 64 hour recording
- Digital shuttle with 6 selectable recording settings
- 5 selectable recording options
- Reverse play option
- Built-in rechargeable back up battery (up to 1 month)
- Record lock prevents unauthorized operation
- Easy to use on screen programming
- Power loss memory (most recent 35 events)
- Warning buzzer alarm signal and end of tape
- Four selectable audio recording settings
- Four selectable recording modes; alarm, panic, repeat and timer
- Instant record check
- Multi-voltage (100 - 240 volts)
- Compatible with most Multiplexer units
- Quick start recording
- Alarm recording mode (most recent 35 events)
- UPC Code 7 78597 07940 1

TECHNICAL SPECIFICATIONS

Item/Model	SG7970	SG7964	SG7940
Recording System	Dual Azimuth, 4 Head	Dual Azimuth, 4 Head	Dual Azimuth, 4 Head
Resolution	Selectable: B&W 300 Color - 250	Selectable: B&W 300 Color - 250	Selectable: B&W 300 Color - 250
RS232C Input Jack	Included	N/A	N/A
Digital Shuttle Speed	6 forward / 6 reverse	6 forward / 6 reverse	6 forward / 6 reverse
Luminance Signal	FM Recording	FM Recording	FM Recording
Recording Speed	SP: L2H, 48H, 72H, 96H, 120H, 168H, 240H, 360H, 480H, 720H, 960H EP: L6H, L18H, L30H SP: L2H	SP: L2H, 48H, 72H, 96H, 120H, 168H, 240H, 360H, 480H, 720H, 960H EP: L6H, L18H, L30H SP: L2H	SP: L2H, 48H EP: L6H, L18H, L30H SP: L2H
Audio Recording	EP: L6H, L18H, L30H SP: L2H	EP: L6H, L18H, L30H SP: L2H	EP: L6H, L18H, L30H SP: L2H
Tape Speed	33.35 m/se (2 hour mode)	33.35 m/se (2 hour mode)	33.35 m/se (2 hour mode)
Fast Forward / Rewind Tape	within 3 minutes T-120	within 3 minutes T-120	within 3 minutes T-120
Video Input/Video Output	1 V p-p, BNC 75 ohms	1 V p-p, BNC 75 ohms	1 V p-p, BNC 75 ohms
Audio Input	-8.8dbm, 47k ohms, RCA	-8.8dbm, 47k ohms, RCA	-8.8dbm, 47k ohms, RCA
Audio Output	-7.8 dbm, less than 1.5kohms, RCA	-7.8 dbm, less than 1.5kohms, RCA	-7.8 dbm, less than 1.5kohms, RCA
Alarm Input	N.O/N.C	N.O/N.C	N.O/N.C
Alarm Output	High/Low	High/Low	High/Low
Operating Temperature	41°F - 104°F	41°F - 104°F	41°F - 104°F
Operating Humidity Range	80% or less	80% or less	80% or less
Power Requirement	Multivoltage 90 - 250V	Multivoltage 90 - 250V	Multivoltage 90 - 250V
Power Consumption	17W	17W	17W
Giftbox Dimensions	17.5" W x 14.5" D x 7.5" H	17.5" W x 14.5" D x 7.5" H	17.5" W x 14.5" D x 7.5" H
Weight	10.5 lbs	10.5 lbs	10.5 lbs

Because our products are subject to continuous improvement, SVC reserves the right to modify product design and specifications without notice and without incurring any obligation. E & O.E.

STRATEGIC

Head Office
300 Alden Road
Markham, Ontario
Canada L3R 4C1
T: (905) 946 8589
F: (905) 947 0138
info@strategicvista.com

WWW.STRATEGICVISTA.COM

LOREX™