

1/3" DIGITAL COLOR AC-24 VOLT CAMERA



WDAC-2400C

- 420 lines of resolution
- 0.3 Lux min. illumination
- Line lock
- Back light compensation
- Isolated built in power transformer

IRIS CONFIGURATION	
VIDEO DRIVE LENS	DC DRIVE LENS
GND NC	DRIVE - CONTROL+
VIDEO DC 9V	DRIVE+ CONTROL-

SPECIFICATION

IMAGE PICK-UP DEVICE	INTERLINE TRANSFER CCD 1/3" FORMAT
TV SYSTEM	NTSC, PAL
NO. OF PIXELS	NTSC = 512(H) • 492(V) PAL = 512(H) • 582(V)
SCANNING SYSTEM	2:1 INTERLACED
SYNC SYSTEM	INTERNAL SYNC
RESOLUTION	420 TV LINE
USABLE ILLUMINATION	0.3 Lux F 1.2
S/N RATIO	MORE THAN 46dB
GAMMA CHARACTERISTIC	0.45
VIDEO OUTPUT	1.0 Vp-p 75 ohm
ELECTRONIC SHUTTER TIME	EIA = 1/60 - 1/100,000 Sec CCIR = 1/50 - 1/100,000 Sec
POWER SUPPLY	DC 12V/AC 24V 60Hz, 50Hz
POWER CONSUMPTION	200mA (MAX) AT DC 12V/AC 24V
LENS	"C" & "CS" MOUNT
OPERATIONAL TEMP.	-10 Deg - +50 Deg C RH95% MAX
STORAGE TEMP.	-20 Deg - +60 Deg C RH95% MAX
DIMENSIONS	50mm(W) • 50mm(H) • 120mm(D)
WEIGHT	APPX. 400 Grs

WELDEX CAN CUSTOMIZE CAMERAS FOR YOUR SPECIFIC NEED!!